

Capillary Thermostats (Single-Phase)

HU/20-127

Type of thermostat: Capillary thermostat
Temperature adjustment range: 20 ÷ 127 (± 4) °C
Capillary material: Copper
Capillary length: 935 (± 20) mm
Sensor dimensions: $\text{Ø}5 \times 130$ mm
Maximum current: 20(4)A / 250V~
Switching hysteresis: 4 ± 2 °C
Maximum sensor temperature: 145 °C
Protection rating: IP00

HU/30-110

Type of thermostat: Capillary thermostat
Temperature adjustment range: 30 ÷ 110 (± 4) °C
Capillary material: Stainless steel
Capillary length: 935 (± 20) mm
Sensor dimensions: $\text{Ø}6 \times 165$ mm
Maximum current: 20(4)A / 250V~
Switching hysteresis: 4 ± 2 °C
Maximum sensor temperature: 125 °C
Protection rating: IP00

HU/5-90

Type of thermostat: Capillary thermostat
Temperature adjustment range: 5 ÷ 90 (± 4) °C
Capillary material: Stainless steel
Capillary length: 935 (± 20) mm
Sensor dimensions: $\text{Ø}6 \times 123$ mm
Maximum current: 20(4)A / 250V~
Switching hysteresis: 4 ± 2 °C
Maximum sensor temperature: 105 °C
Protection rating: IP00

HU/50-220

Type of thermostat: Capillary thermostat
Temperature adjustment range: 50 ÷ 220 (± 8) °C
Capillary material: Stainless steel
Capillary length: 935 (± 20) mm
Sensor dimensions: $\text{Ø}4 \times 140$ mm

Maximum current: 20(4)A / 250V~

Switching hysteresis: 10 ± 2 °C

Maximum sensor temperature: 240 °C

Protection rating: IP00

HU/50-320

Type of thermostat: Capillary thermostat

Temperature adjustment range: $50 \div 320 (\pm 10/-2)$ °C

Capillary material: Stainless steel

Capillary length: $935 (\pm 20)$ mm

Sensor dimensions: $\varnothing 3 \times 166$ mm

Maximum current: 20(4)A / 250V~

Switching hysteresis: 8 ± 2 °C

Maximum sensor temperature: 350 °C

Protection rating: IP00